

Product Features

Item	Spec.	Remarks
Product structure	G+G	
AVdimensiondescription	27 寸	
V. A. Size	597.9*336.3mm(±0.3mm)	
Total Thickness	3.3mm (±0.3mm)	
Outline Dimension	653.3*391.7mm(-0.3mm)	Black screen printing
O.D. Fillet	R10.8mm(±0.3mm)×4	
Coverlens Thickness	2.0mm(±0.1mm)	
ITO Glass Size	618.0*355.7mm(±0.3mm)	
ITO Glass Thickness	1.1mm(±0.05mm)	

Electrical structure

Item	Spec.	Remarks
Sensing IC	ILI2312/SIS9519	
Number of Channels	RX78*TX44	
Support Contact	10	
Number of Touch Keys	0	
Interface form	USB	
Work voltage	5V	

Environmental Characteristics

Item	Temperature	Humidity
Operating	-20-60℃	20%RH-90%RH
Storage	-30-70℃	10%RH-90%RH

Optical and mechanical properties

Item	Spec.	Remarks
Transparency	$\geq 85\%$	
Haze	$\leq 3\%$	
Surface hardness	6H(Apply a force of 500g.)	
Falling ball	Falling ball	$\geq 50\text{cm}$, 64g Steel ball

Remark:

1. It is not the defect that the dust from the environment.
2. It is not the defect that the damage caused by teardown.

Precautions during the assembly

1. Cautions for Storage

Store per the temp. & humidity requirements in the Sample Approval Sheet. Avoid direct sunlight and heavy pressure.

2. Cautions for unpacking

- 2.1 Minimize handling frequency.
- 2.2 Use handling tools whenever possible.
- 2.3 Max. stacking: 3 layers. Handle with care and place upright.

3. Assembly precautions

- 3.1 Do not apply excessive pulling force to the product.
- 3.2 To maintain product clarity, wear finger cots or gloves before handling. Caution: glass edges/corners.
- 3.3 When picking up, do not pull the FPC or hold corners with one hand—excessive force may cause bubbles/delamination.
- 3.4 During assembly, do not forcefully pull the FPC, as it may peel off.
- 3.5 Do not pull the FPC sideways—side force may cause cracking. Maintain a 0.2 - 0.5mm gap with our TP.
- 3.6 Follow ESD protection during production to prevent damage.